



MOD C: OPEN FLUE
MOD F: ROOM SEALED

FL D

Instant combi wall-hung boiler

- Traditional compact wall hung boiler for central heating and domestic hot water
- Monothermic CH exchanger plus DHW stainless steel plates exchanger fed by diverting valve
- Complete and intuitive control board, with autodiagnostic function, featuring backlit display and setting buttons
- Can be connected to outdoor probe and remote control, as optionals
- Modulating operation both in heating and domestic hot water mode, with adjustable temperature increase slope
- Hydraulic bypass as a standard
- Antifrost function, if gas and power supplied
- Compact dimensions thus enabling installation, also in place where limited space is available
- Ready for connection to solar systems: integrated management of combined DHW production through boiler and solar system

Boiler code Boiler model

ODAC4ZYD **FL D C 24**


ODAC7ZYD **FL D C 32**

ODAF4ZYD **FL D F 24**

ODAF7ZYD **FL D F 32**

ODAF8ZYD **FL D F 37**

WATER SCHEME



MODEL			C 24	C 32	F 24	F 32	F 37
Heat input	Max	kW	25.8	34.4	25.8	34.4	39.7
	Min	kW	8.3	11.5	8.3	11.5	14.0
Heat output	Max	kW	23.5	31.3	24.0	32.0	37.0
	Min	kW	7.0	9.7	7.2	9.9	12.9
Efficiency	80°C - 60°C	Pmax %	91.0	91.0	93.0	93.1	93.2
	30% load	%	89.6	89.8	90.5	91	91
DHW production	Δt 25°C	l/min	13.4	17.9	13.7	18.3	21.1
	Δt 30°C	l/min	11.2	14.9	11.4	15.2	17.6
Heating operating pressure	Max	bar	3	3	3	3	3
Empty weight		kg	27	30	32	35	37
Dimensions	WxHxD	mm	400x700x330	400x700x330	400x700x330	400x700x330	450x700x330